

Lining
04.84100804-0001

Fixture details

| | |
|-----------------|-----------------|
| Mounting | Pendant |
| Light emission | Direct-Indirect |
| Fitting cover | satin diffusor |
| Protection rate | IP 20 |
| Housing | Aluminium |
| Finish | anodized finish |
| Certificates | CE, ISO 9001 |



Electric details

| | |
|------------------|----------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Current driver |

Lamp details

| | |
|---------------------|-----------------------------|
| Lamptype | LED 4000K |
| Wattage | 6,7W |
| Gross luminous flux | 26600 |
| Luminaire power | 152,9W |
| Number | 10 |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 + 10x LED 4000K 7,2W |

Photometric details

| | |
|-----------------------|----------------|
| UGR | >19 |
| CIE Fluxcode | 49 80 96 99 65 |
| CIE Fluxcode Indirect | 00 00 00 00 73 |

Dimensions

| | |
|---|---------|
| A | 2894 mm |
| B | 60 mm |
| C | 200 mm |

Remarks

Suspended luminaire - Direct - HO 225mA - satin (flush) - ANO



ENERGY

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

WXYZ
kWh/1000h

MULTILINE®

2019/2015