

**T-Line 130 - Direct or Indirect - curved cover panel - ANO**  
06.37200054-0001

**Fixture details**

|                 |                         |
|-----------------|-------------------------|
| Mounting        | Wall                    |
| Light emission  | Direct or Indirect      |
| Fitting cover   | Prismatic diffuser      |
| Protection rate | IP 20                   |
| Housing         | Aluminium/Polycarbonate |
| Finish          | anodized finish         |
| Certificates    | CE, ISO 9001            |



**Electric details**

|                  |                |
|------------------|----------------|
| Protection class | I              |
| Supply           | 230V           |
| Control gear box | Current driver |

**Lamp details**

|                     |                  |
|---------------------|------------------|
| Lamptype            | LED 4000K        |
| Wattage             | 3,6W             |
| Gross luminous flux | 3350             |
| Luminaire power     | 19,8W            |
| Number              | 5                |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance     | MacAdam 3        |
| CRI                 | >80              |

**Photometric details**

|                       |                 |
|-----------------------|-----------------|
| CIE Fluxcode          | 70 93 99 100 71 |
| CIE Fluxcode Indirect | 00 00 00 00 71  |

**Dimensions**

|   |         |
|---|---------|
| A | 1434 mm |
|---|---------|

**Remarks**

direct or indirect light distribution with curved cover



**ENERGY**

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**WXYZ**  
kWh/1000h

**MULTILINE®**

2019/2015