

Rekta 30 SAPP - satin - HO 325mA - RAL
07.23004624-9999

Fixture details

| | |
|-----------------|---------------------------|
| Mounting | Ceiling recessed |
| Light emission | Direct |
| Fitting cover | satin diffusor |
| Protection rate | IP 20 |
| Housing | Aluminium |
| Finish | RAL colour at your choice |
| Certificates | CE, ISO 9001 |



Electric details

| | |
|------------------|------------------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Current driver DALI/TD |

Lamp details

| | |
|---------------------|------------------|
| Lamptype | LED 4000K |
| Wattage | 7,2W |
| Gross luminous flux | 2680 |
| Luminaire power | 15,8W |
| Number | 2 |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 |

Photometric details


| | |
|--------------|-----------------|
| UGR | 28,0/28,3 |
| CIE Fluxcode | 50 80 96 100 67 |

Dimensions

| | |
|---|--------|
| A | 564 mm |
|---|--------|

Remarks

satin LED diffusor 325mA



ENERGY

A
 Verkrijgbaar op aanvraag.
B
 Disponible sur demande.
C
D
 Available on request.
E
 Auf Anfrage.
G

WXYZ
kWh/1000h

MULTILINE® 2019/2015