

Rekta 80x100 Direct - satin - HO 150mA - RAL
07.68000554-9999

Fixture details

| | |
|-----------------|---------------------------|
| Mounting | Ceiling recessed |
| Light emission | Direct |
| Fitting cover | satin diffusor |
| Protection rate | IP 20 |
| Housing | Aluminium |
| Finish | RAL colour at your choice |
| Certificates | CE, ISO 9001 |

Electric details

| | |
|------------------|----------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Current driver |

Lamp details

| | |
|---------------------|------------------|
| Lamptype | LED 4000K |
| Wattage | 3,2W |
| Gross luminous flux | 3350 |
| Luminaire power | 17,6W |
| Number | 5 |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 |

Photometric details

| | |
|--------------|-----------------|
| UGR | >19 |
| CIE Fluxcode | 54 83 97 100 69 |

Dimensions

| | |
|---|---------|
| A | 1404 mm |
|---|---------|

Remarks

Recessed luminaire (trimless) - Direct - HO 150mA - satin - RAL



ENERGY

A
 Verkrijgbaar op aanvraag.
B
 Disponible sur demande.
C
D
 Available on request.
E
F
 Auf Anfrage.
G

WXYZ
kWh/1000h

MULTILINE® 2019/2015