

Score flat Direct - satin - HO 150mA - ANO
04.87004504-0001

Fixture details

| | |
|-----------------|-----------------|
| Mounting | Pendant |
| Light emission | Direct |
| Fitting cover | satin diffusor |
| Protection rate | IP 20 |
| Housing | Aluminium |
| Finish | anodized finish |
| Certificates | CE, ISO 9001 |

Electric details

| | |
|------------------|------------------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Current driver DALI/TD |

Lamp details

| | |
|---------------------|------------------|
| Lamptype | LED 4000K |
| Wattage | 3,2W |
| Gross luminous flux | 6700 |
| Luminaire power | 35,2W |
| Number | 10 |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 |

Photometric details

| | |
|--------------|----------------|
| UGR | >19 |
| CIE Fluxcode | 56 88 98 99 71 |

Dimensions

| | |
|---|---------|
| A | 2824 mm |
|---|---------|

Remarks

Suspended luminaire - Direct - HO 150mA - satin - ANO



ENERGY

Verkrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

WXYZ
kWh/1000h

MULTILINE®

2019/2015