

Tube 70 T1 - satin - HO 150mA - standard
35.90015544-0000

Fixture details

| | |
|-----------------|--------------------|
| Mounting | Wall |
| Light emission | Diffus |
| Fitting cover | satin diffusor |
| Protection rate | IP 65 |
| Housing | Polycarbonate/PMMA |
| Finish | frosted |
| Certificates | CE, ISO 9001 |



Electric details

| | |
|------------------|------------------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Current driver DALI/TD |
| Emergency set | Autonomy 1 hour DALI |

Lamp details

| | |
|---------------------|------------------|
| Lamptype | LED 4000K |
| Wattage | 3,2W |
| Gross luminous flux | 2680 |
| Luminaire power | 14,1W |
| Number | 4 |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 |

Photometric details

| | |
|--------------|----------------|
| CIE Fluxcode | 45 74 91 93 85 |
|--------------|----------------|

Dimensions

| | |
|---|---------|
| A | 1200 mm |
|---|---------|

Remarks

Wall luminaire - satin - HO 150mA - standard



ENERGY

Verkrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

WXYZ
kWh/1000h

MULTILINE®

2019/2015