

Re-LED Direct - MPO - HO 325mA - ANO  
04.91014604-0001

#### Fixture details

|                 |                          |
|-----------------|--------------------------|
| Mounting        | Pendant                  |
| Light emission  | Direct                   |
| Fitting cover   | micro prismatic diffuser |
| Protection rate | IP 20                    |
| Housing         | Aluminium                |
| Finish          | anodized finish          |
| Certificates    | CE, ISO 9001             |

#### Electric details

|                  |                        |
|------------------|------------------------|
| Protection class | I                      |
| Supply           | 230V                   |
| Control gear box | Current driver DALI/TD |

#### Lamp details

|                     |                  |
|---------------------|------------------|
| Lamptype            | LED 4000K        |
| Wattage             | 7,1W             |
| Gross luminous flux | 14250            |
| Luminaire power     | 78,6W            |
| Number              | 10               |
| Lifetime LED module | L80/B10 > 72000h |
| Color tolerance     | MacAdam 3        |
| CRI                 | >80              |

#### Photometric details

|              |                 |
|--------------|-----------------|
| UGR          | >19             |
| CIE Fluxcode | 58 89 98 100 54 |

#### Dimensions

|   |         |
|---|---------|
| A | 2810 mm |
|---|---------|

#### Remarks

Suspended luminaire - Direct - HO 325mA - MPO - ANO

