

Sferio Direct - satin - LO - IP54 - RAL 9003
35.36002024-9003

Fixture details

| | |
|-----------------|-----------------------|
| Mounting | Ceiling |
| Light emission | Direct |
| Fitting cover | Opal diffuser |
| Protection rate | IP 54 |
| Housing | Aluminium |
| Finish | RAL 9003 Signal white |
| Certificates | CE, ISO 9001 |



Electric details

| | |
|------------------|----------------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Current driver 1-10V |

Lamp details

| | |
|-------------------------|------------------|
| Lamptype | LED 4000K |
| Wattage | 13W |
| Luminaire power | 13W |
| Luminaire luminous flux | 1790 |
| Number | 1 |
| Lifetime LED module | L80/B10 = 50000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 |

Photometric details


| | |
|--------------|------------------|
| UGR | >19 |
| CIE Fluxcode | 47 78 95 100 100 |

Dimensions

| | |
|---|--------|
| A | 400 mm |
|---|--------|

Remarks

Ceiling luminaire - Direct - satin - LO - IP54 - RAL 9003



ENERGY

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

WXYZ
kWh/1000h

MULTILINE®

2019/2015