

Scorta Direct - satin - HO - ANO
04.86004233-0001

Fixture details

| | |
|-----------------|-----------------|
| Mounting | Pendant |
| Light emission | Direct |
| Fitting cover | Opal diffuser |
| Protection rate | IP 20 |
| Housing | Aluminium |
| Finish | anodized finish |
| Certificates | CE, ISO 9001 |



Electric details

| | |
|------------------|-------------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Power supply DALI |



Lamp details

| | |
|-------------------------|------------------|
| Lamptype | LED 3000K |
| Wattage | 51W |
| Luminaire power | 51W |
| Luminaire luminous flux | 6536 |
| Number | 1 |
| Lifetime LED module | L80/B10 = 50000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 |

Photometric details

| | |
|--------------|------------------|
| UGR | >19 |
| CIE Fluxcode | 46 77 94 100 100 |

Dimensions

| | |
|---|--------|
| A | 530 mm |
|---|--------|

Remarks

Suspended luminaire - Direct - satin - HO - ANO



ENERGY

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

WXYZ
kWh/1000h

MULTILINE®

2019/2015