

Anilo Direct - MPO - HO - RAL 9003
05.49012274-9003

Fixture details

| | |
|-----------------|--------------------------|
| Mounting | Ceiling |
| Light emission | Direct |
| Fitting cover | micro prismatic diffuser |
| Protection rate | IP 20 |
| Housing | Aluminium |
| Finish | RAL 9003 Signal white |
| Certificates | CE, ISO 9001 |



Electric details

| | |
|------------------|----------------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Current driver 1-10V |

Lamp details

| | |
|-------------------------|------------------|
| Lamptype | LED 4000K |
| Wattage | 259W |
| Luminaire power | 259W |
| Luminaire luminous flux | 24400 |
| Number | 1 |
| Lifetime LED module | L80/B10 = 50000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 |

Photometric details

| | |
|--------------|------------------|
| UGR | <19 |
| CIE Fluxcode | 56 84 97 100 100 |

Dimensions

| | |
|---|---------|
| A | 4000 mm |
|---|---------|

Remarks

Ceiling luminaire - Direct - MPO - HO - RAL 9003



ENERGY

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

MULTILINE® **WXYZ** kWh/1000h

2019/2015