

Anilo Direct - MPO - HO - RAL 9003  
05.49012294-9003

**Fixture details**

|                 |                          |
|-----------------|--------------------------|
| Mounting        | Ceiling                  |
| Light emission  | Direct                   |
| Fitting cover   | micro prismatic diffuser |
| Protection rate | IP 20                    |
| Housing         | Aluminium                |
| Finish          | RAL 9003 Signal white    |
| Certificates    | CE, ISO 9001             |



**Electric details**

|                  |                      |
|------------------|----------------------|
| Protection class | I                    |
| Supply           | 230V                 |
| Control gear box | Current driver 1-10V |

**Lamp details**

|                         |                  |
|-------------------------|------------------|
| Lamptype                | LED 4000K        |
| Wattage                 | 414W             |
| Luminaire power         | 414W             |
| Luminaire luminous flux | 39040            |
| Number                  | 1                |
| Lifetime LED module     | L80/B10 = 50000h |
| Color tolerance         | MacAdam 3        |
| CRI                     | >80              |

**Photometric details**

|              |                  |
|--------------|------------------|
| UGR          | <19              |
| CIE Fluxcode | 56 84 97 100 100 |

**Dimensions**

|   |         |
|---|---------|
| A | 6000 mm |
|---|---------|

**Remarks**

Ceiling luminaire - Direct - MPO - HO - RAL 9003



**ENERGY**

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

**MULTILINE®** **WXYZ**  
kWh/1000h

2019/2015