

Grip T1 - Direct - satiné - 100mA - RAL
05.43000244-9999

Fixture details

| | |
|-----------------|---------------------------|
| Mounting | Ceiling |
| Light emission | Direct |
| Fitting cover | satin diffusor |
| Protection rate | IP 20 |
| Housing | Aluminium |
| Finish | RAL colour at your choice |
| Certificates | CE, ISO 9001 |



Electric details

| | |
|------------------|----------------|
| Protection class | I |
| Supply | 230V |
| Control gear box | Current driver |

Lamp details

| | |
|---------------------|------------------|
| Lamptype | LED 4000K |
| Wattage | 4,0W |
| Gross luminous flux | 3020 |
| Luminaire power | 17,6W |
| Number | 4 |
| Lifetime LED module | L90/B50 > 50000h |
| Color tolerance | MacAdam 3 |
| CRI | >80 |

Photometric details

| | |
|--------------|----------------|
| UGR | >19 |
| CIE Fluxcode | 50 80 96 99 66 |

Dimensions

| | |
|---|---------|
| A | 1130 mm |
| B | 810 mm |

Remarks

Ceiling



ENERGY

Verrijgbaar op aanvraag.

Disponible sur demande.

Available on request.

Auf Anfrage.

MULTILINE® **WXYZ**
kWh/1000h

2019/2015